



Cold Water Pressure Washers

## Cold Water Base Mount Electric Models



- ◆ Triplex plunger pump with ceramic plungers and stainless steel valves.
- ◆ Adjustable pressure
- ◆ Chemical Injection
- ◆ 50' non-marking hose
- ◆ Trigger Gun
- ◆ Heavy duty wand with quick change tips in 0°, 15°, 25°, 40° soap tip
- ◆ Totally enclosed motor
- ◆ Look for optional accessories like the swivel hose reel with wall mounting bracket



Model	PSI/bar	GPM/lpm	HP	Voltage /amp/phase	Pump Max. Temp.	Thermal	Dimensions L x W x H	Ship Weight
1500GE	1500 / 103.5	3 / 11.4	3	230 Volt / 20 Amp / 1	140° F	Mechanical	28" x 20" x 13"	86 lbs.
2000GEAR	2000 / 138	4 / 15.2	5	230 Volt / 26 Amp / 1	160° F	Mechanical	28" x 20" x 13"	150 lbs.
2000GE	2000 / 138	4 / 15.2	5	230 Volt / 26 Amp / 1	160° F	Mechanical	28" x 20" x 13"	150 lbs.
3000GEAR	3000 / 207	4 / 15.2	7.5	230 Volt / 34 Amp / 1	160° F	Mechanical	28" x 20" x 13"	180 lbs.
3000GE	3000 / 207	4 / 15.2	7.5	230 Volt / 34 Amp / 1	160° F	Mechanical	28" x 20" x 13"	180 lbs.
2500GE	2500 / 172.5	5.8 / 22	10	230 Volt / 40 Amp / 1	160° F	Mechanical	30" x 18" x 15"	240 lbs.
208GE	2000 / 138	8 / 30.4	10	230 Volt / 40 Amp / 1	160° F	Mechanical	30" x 18" x 15"	240 lbs.
2545STAT	2500 / 172.5	4.5 / 17.1	7.5	230 Volt / 34 Amp / 1	160° F	Mechanical	40" x 24" x 47"	300 lbs.
3040STAT	3000 / 207	4 / 15.2	7.5	230 Volt / 34 Amp / 1	160° F	Mechanical	40" x 24" x 47"	300 lbs.
208STAT	2000 / 138	8 / 30.4	10	230 Volt / 40 Amp / 1	160° F	Mechanical	40" x 24" x 47"	325 lbs.
2555STAT	2500 / 172.5	5.5 / 20.9	10	230 Volt / 40 Amp / 1	160° F	Mechanical	40" x 24" x 47"	325 lbs.

\*\*\*All electric models shown are available in Three Phase upon request.\*\*\*