

Cam Spray SK Series Hot Water Trailer Jetters



Working well under pressure!

- Triplex Industrial Pump.
- 400' x 1/2' Hose on a 12 VDC variable speed electric reel with remote forward and reverse foot switch, this hose is used for cold water jetting.
- 250' x 3/8" Hose on Manual Reel used for hot water jetting.
- 300 gallon tank with run dry shutdown switch.
- 2" Hydrant Fill.
- 2500 watt on board generator.
- Trailer with Powder Coat Finish, 7000# axle, 15" Chrome Wheels, 6 bolt hubs and brakes.
- 2 Nozzle sets with box and tip cleaner, one for the 3/8" jet hose and one for the 1/2" jet hose.
- Pressure gauge.
- Lockable tool boxes, front and rear.
- Tool box with gloves and face shield.
- Power Pulse Valve.
- Remote Throttle control.
- Hour Meter.
- Safety Vest
- Strobe light with 5' extension.
- Measures 156" Long x 72" Wide x 64" High.
- Schedule 80 coil with Stainless Steel cold wrap.
- Burner runs on kerosene or diesel fuel and provides hot water for the 3/8" drain line.



Model SK2511B-Hot	23 h.p. Briggs and Stratton Engine	11 gpm @ 2500 psi
Model SK2511H-Hot	24 h.p. Honda Engine	11 gpm @ 2500 psi
Model SK2511D-Hot	20 h.p. Lombardini Diesel	11 gpm @ 2500 psi